



# PATCH KIT

Cal Dorado Stucco Patch is a Portland cement based patching material for the maintenance of stucco finishes. Cal Dorado Stucco Patch is preblended to match each of our colors.

## **SURFACE PREPARATION**

All surfaces must be free of debris, dirt and dust, grease, oils, curing agents, and cleaning solutions. Glossy or painted surfaces must be sanded and cleaned to ensure a proper bond. Repair all pre-existing cracks. Just prior to application, dampen all surfaces with clean water.

## **MIXING**

1. Combine 1/3 gallons (1.26 L) of clean water per pail of El Dorado Stucco Patch and mix for about 3 minutes.
2. Let stand for 5 minutes, then stir again for 3 minutes and use.
3. Add only the amount of additional water necessary to bring the stucco to a workable consistency.

## **APPLICATION**

Float or spray Cal Dorado Stucco Patch into place and texture to desired finish. In excessively hot or dry conditions, a light spray of clean water is recommended over the patch to prevent cracking.

## **CURING**

Cal Dorado Stucco Patch should fully cure in 7 days. Curing time may vary due to ambient temperature or thickness of material.

## **CLEANING**

Clean all tools with water immediately after use.

## **COVERAGE**

Coverage will vary depending on application method. Approximate coverage per 10 lb. (4.5 kg) pail: 3 - 4 sq. ft. (0.3m<sup>2</sup> to 0.4m<sup>2</sup>).

## **PACKAGING**

- Cal Dorado Stucco Patch is packaged in 10 lb. (4.5 kg) pails.
- 30 colors to choose from.

## **LIMITATIONS**

Do not apply Cal Dorado stucco when the ambient and surface temperature is below 40°F/4°C. Do not apply to substrates which are frozen or contain frost/ice. Do not apply Cal Dorado stucco in the rain or when rain is expected within 48 hours. In excessively hot or dry conditions, a light spray of clean water is recommended over the stucco finish to prevent cracking. DO not add any other materials to the mixture of Cal Dorado stucco products. Failure to follow these instructions could result in cracking, chipping, discoloration, or peeling. Due to job conditions beyond the control of Western States Wholesale, Inc. we make no warranty as to the acceptance of the final color.

## **SAFETY**

Contains Portland cement. Wear rubber gloves and eye protection. Avoid eye contact or prolonged contact with skin. If eye contact occurs, flush with water for 15 minutes. Consult physician immediately. This product contains free silica. Do not breathe dust; wear NIOSH approved respirator.

**KEEP OUT OF REACH OF CHILDREN.  
DO NOT TAKE INTERNALLY.**