



CEMENT

PRODUCT DESCRIPTION

RapidCrete™ Cement is a dry hydraulic cement. It is a replacement for Portland cement. Mix with suitable aggregate to achieve fast setting, high strength results.

SURFACE PREPARATION

Surface must be clean and free from dirt, loose debris, oil, sealers, and other contaminants that will prevent a good bond. Glossy or painted surfaces must be roughened and cleaned. Immediately prior to application, the repair surfaces must be thoroughly saturated with water, but leave no standing water.

MIXING

Mix RapidCrete™ Cement with your dry aggregates. Pre blend dry before adding water. Add water to achieve desired consistency for job requirements.

CURING

Under normal conditions at 70°F (21°C), RapidCrete™ Cement will begin to set in 15 minutes and achieve full strength after approximately 1 hour. Temperatures may affect working and curing times.

CLEAN-UP

Clean with water before material dries.

PACKAGING

• 88 LBS. (39.9 KG) Bag

STORAGE

Store in a cool dry area. Keep from freezing.

SAFETY

Contains Portland cement. Wear rubber gloves and eye protection. Avoid eye contact or prolonged contact with skin. If eye contact occurs, flush with water for 15 minutes. Consult physician immediately. This product contains free silica. Do not breathe dust; wear NIOSH approved respirator. KEEP OUT OF REACH OF CHILDREN. DO NOT TAKE INTERNALLY.

WARNING

Western States Wholesale, as blender of processed material in the State of California, we are required by Proposition 65 to warn that one or more of the components in this product, contains chemicals known to the State of California, to cause cancer, birth defects, or other reproductive harm.