



CONCRETE

SECTION I – IDENTITY

MANUFACTURER

Western States Wholesale
1420 S. Bon View, Ontario, CA 91761
Emergency Phone: (800) 325-6851

TRADE NAME

Rapid Crete – Concrete

CHEMICAL FAMILY

Calcium Salts

FORMULA

2CaO.SiO₂

4CaO.Al₂O₃.Fe₂O₃

CaSO₄

4CaO.3Al₂O₃.SO₃

Small amounts of CaO, CaCO₃, may be present.

Small amounts of MgO, and trace amounts of K₂SO₄ and Na₂SO₄ also may be present.

Other Salts

Gypsum

CaSO₄.2H₂O

Crystalline Silica

Kaolin

Talc

Formaldehyde

CAS#

(CAS# 10034-77-2)

(CAS# 12068-35-8)

(CAS# 13397-24-5)

(CAS# 14808-60-7)

(CAS# 1332-58-7)

(CAS# 14807-96-6)

(CAS# 000050-00-0)

SECTION II – HAZARDOUS INGREDIENTS

Portland cement is classified merely as a nuisance dust by OSHA (29 CFR 1910.1000, Table Z-3), MSHA (30 CFR 56.5001), ACGIH (TLVs for 1973, Appendix E), and ACGIH (TLVs for 1985-89, Appendix D). Portland cement is NOT listed by NTP, IARC, or OSHA as containing carcinogens. Food and Drug Administration [CFR Title 21, v.3, sec 184.1230] – Calcium Sulfate is Generally Recognized as Safe (GRAS). Respirable crystalline silica: IARC: Group 1 carcinogen, NTP: Known human carcinogen. Formaldehyde is classified as hazardous under OSHA.

SECTION III – PHYSICAL DATA

Boiling Point: Not applicable

Vapor Pressure: Not applicable

Vapor Density: Not applicable

Solubility in Water: Slight (0.1-1.0%)

Specific Gravity: 2.65 - 3.00

Percentage Volatiles by Volume: 0%

Evaporation Rate: Not applicable

Appearance and Odor: Grey or white powder; no odor.

SECTION IV – HAZARDOUS INGREDIENTS

Flash Point: RapidCrete is noncombustible and non-explosive.

Flammable or Explosive Limits: Not applicable.

Extinguishing Media: Not applicable.

Threshold Limit Value: Respirable Dust-5mg/m³ Total Dust - 10mg/m³

Emergency and First Aid Procedures: Irrigate eyes with water; consult physician.

Wash exposed skin areas with soap and water.

Special Firefighting Procedures: Not applicable.

Unusual Fire and Explosion Hazards: None

Effects of Overexposure:

Acute: Wet cement, especially as an ingredient in plastic (unhardened) concrete, can dry the skin and cause alkali burns. Cement dust can irritate the eyes and upper respiratory system.

Chronic: Cement dust can cause inflammation of the lining tissue of the interior of the nose and Hypersensitive individuals may develop an allergic dermatitis (skin rash).

SECTION V – REACTIVITY DATA

Stability: Product is stable. Keep dry until used.

Hazardous Decomposition Products: None

Incompatibility: None

Hazardous Polymerization: Will not occur

SECTION VI – SPILL PROCEDURES

Steps to be Taken if Material is Spilled: Use dry clean-up methods.

Waste Disposal Method: Material can be returned to dispense the dust into the air container for later use, or it can be disposed of as a common waste.

SECTION VII – SPECIAL PROTECTION INFORMATION

Respiratory Protection: In dusty environments, use a NIOSH approved respirator.

Ventilation: Exhaust fans to control airborne dust levels.

Eye Protection: In dusty environments, use tight-fitting goggles.

Skin Protection: Use barrier creams, gloves, boots, and clothing to protect the skin from prolonged contact with wet cement, especially in plastic (unhardened) concrete. Immediately after working with cement, workers should shower with soap and water. Precautions must be observed because wet cement burns with little warning – little heat is sensed.

SECTION VIII – SPECIAL PRECAUTIONS

Precautions to be Taken in Handling and Storing: None (See Section VIII).

Other Precautions: None.

SECTION IX – ABBREVIATIONS

ACGIH: American Conference of Governmental Industrial Hygienists

MSHA: Mine Safety and Health Administration

CAS: Chemical Abstract Service

NIOSH: National Institute for Occupational Safety and Health

CFR: Code of Federal Regulations

NTP: National Toxicology Program

IARC: International Agency for Research on Cancer

OSHA: Occupational Safety and Health Administration

m³: Cubic meter

TLVs: Threshold limit values

mg: Milligram