

f † n.!.k  
" z0n³

(\$6</2&. %\$6( 3\$1(/  
\$/7(51\$7-9( %\$6( 6<

67\$%-/-7< 3(5)250  
'5\$-1\$\*(  
\$// -1 21(

f † n.!.k  
«°5ü•¬°@ « ¬øM

(DV\RFN %DVH 3DQHOV DUH DQ DOWHUQD  
DJJUHJDWH URFN WKDW FDQ EH LQVWDOO  
(DV\RFN %DVH 3DQHOV SURYLGH D VROLG  
IRXQGDWLRQ DORQJ ZLWK VXSHULRU GUDL

9HUWLFDO /RFNLQJ 6\VWH  
5HGXFHV -QVWDOODWLRQ  
%XLQW([SDQVLRQ &RQW  
6XSHULRU 'UDLQDJH  
/LPLWHG /LIHWLPH :DUUD  
3HUIHFW IRU /DQGVFDSLQ  
3OD\JURXQG 3HW DQG )LHQ  
-QVWDOODWLRQV  
'UDPDWLFDOO\ 5HGXFHV \$P  
\*URXQGZRUN 1HHGHG  
ODGH LQ 86\$ RI 5HF\FODEO

HDV\ORFNSDQHOV FRP

7UH\ 3DU  
'LUHFWRU RI  
WUH\#HDV\ORFNSD

# EASYLOCK PANELS

## EASYLOCK BASE PANEL SPECS

### MATERIAL

Material	Recyclable HDPE
UV Stabilization	Limited Carbon Black

### PRODUCT

Shape	Hexagonal cell structure
Anti-Slip System	Min 571 anti-slip triangles per panel
Locking System	Clicking system
Dimensions	30.375" x 23" x 0.875" (1 Panel = 4.85 sq ft)
Weight	4.5 lbs per panel; 0.93 lbs per sq ft

### TESTING

GMAX value	151 (panel only on concrete)*
Load Capacity	374 psi up to 998 psi
Vertical drainage	4,068" per/hr
Horizontal drainage	1,673" per/hr
Water storage capacity	1.98 gallons per panel
Expansion	Less than 0.03" movement in all directions
Slip resistance	2x higher than crushed stone

\* GMAX values vary depending on materials below and turf system above the EasyLock Base Panels

## EASYLOCK ADVANTAGE

More and more installers are realizing rock is not always the best option for base work under artificial grass. **EasyLock Base Panels** are the best base replacement system option available on the market. It saves time, saves wear and tear on machines or rental costs, and eliminates the need for excavating large volumes of dirt. Perfect for rooftops, playgrounds, pets, sports fields, and landscaping projects, **EasyLock Base Panels** are the perfect base alternative.

**Trey Parker**  
Director of Sales  
trey@easylockpanels.com

405-503-2680

easylockpanels.com